

**Thiele-Small Parameters.**

Suggested Enclosure: Sealed

Ported



Model:	<b>V-1250SNI</b>	
Cone Dia:	300	(mm)
Re (VC):	3.93	(ohms)
Fo:	33.4087	(Hz)
Z <sub>max</sub> :	37.9993	(ohms)
S <sub>d</sub> :	0.0433m <sup>2</sup>	(sqm)
BL:	11.6214	(TM)
N <sub>o</sub> :	0.4019	(1/100)
SPL <sub>o</sub> :	88.0589	(dB)
Q <sub>ms</sub> :	4.9922	
Q <sub>es</sub> :	0.5759	
Q <sub>ts</sub> :	0.5163	
V <sub>as</sub> :	64.1781	(liters)
C <sub>ms</sub> :	240.7197	(uM/N)
M <sub>ms</sub> :	94.2777	(g)
M <sub>md</sub> :	89.0915	(g)
L <sub>evc@1K</sub> :	2.1352	(mH)
R <sub>em@1K</sub> :	4.2999	(ohms)
K <sub>rm</sub> :	2.0464	(mΩ)
K <sub>xm</sub> :	48.3153	(mH)
E <sub>rm</sub> :	0.8748	
E <sub>xm</sub> :	0.6433	
X <sub>max</sub> :	10mm	(mm)
P <sub>max</sub> :	700W	Watts
EBP :	58.01128668	
V <sub>d</sub> :	0.043	Ft <sup>3</sup>

Note: Specifications subject to change without prior notice.