

Model:	07CVR82	07CVR84
Norm Imp	4.00	8.00
SPL	83.35	83.16
Lem	3.015	4.520
Reve	4.05	7.70
Sd	0.0214	0.0214
BL	9.99	12.41
Vas	12.04	12.13
Mms	67.90	62.57
Fs	44.9	46.7
Qms	10.443	10.377
Qes	0.778	0.893
Qts	0.725	0.843

Model:	07CVR102	07CVR104
Norm Imp	4.00	8.00
SPL	84.88	85.12
Lem	3.751	5.906
Reve	3.54	6.98
Sd	0.0379	0.0379
BL	12.57	16.42
Vas	22.20	22.09
Mms	135.70	122.90
Fs	41.5	43.6
Qms	9.481	9.489
Qes	0.791	0.872
Qts	0.730	0.799

Model:	07CVR122	07CVR124
Norm Imp	4.00	8.00
SPL	86.71	86.74
Lem	3.759	5.793
Reve	3.55	7.16
Sd	0.0531	0.0531
BL	14.05	18.26
Vas	83.40	90.51
Mms	171.75	160.85
Fs	26.7	26.5
Qms	9.197	8.592
Qes	0.518	0.554
Qts	0.491	0.521

Model:	07CVR152	07CVR154
Norm Imp	4.00	8.00
SPL	90.17	89.85
Lem	4.968	7.565
Reve	3.60	6.80
Sd	0.2863	0.0881
BL	20.33	25.82
Vas	164.41	153.12
Mms	275.2	264.00
Fs	24.9	26.3
Qms	10.498	10.262
Qes	0.375	0.445
Qts	0.362	0.426

Model:	05CVR152	05CVR122	05CVR102	05CVR82
Nominal Impedance:	2	2	2	2
SPL dB 1W/1M:	90.2	85.7	88.8	86.5
Displacement, cc:	3992	2001	1234	674
Displacement, cu.in.:	243.6	122.1	75.3	41.1
Hole cutout, in dia:	13 7/8	11 1/8	9 1/4	7 1/16
Mounting Depth, in.:	8 1/8	6 5/16	5 9/16	4 5/16
Revc:	3.64	3.52	3.53	4.12
VC Inductance, mH:	4.068	3.419	3.25	2.767
Sd, SqM:	0.0881	0.0531	0.0379	0.0214
BL:	20.81	12.98	12.87	9.65
Vas, Liters:	185.9	99.66	25.03	12.8
Vas, CuFt:	6.56	3.52	0.88	0.45
Mms, gms:	279.27	184.26	135.4	67.5
Fs:	23.2	23.5	39	43.7
Qms:	10.37	8.813	9.579	9.528
Qes:	0.342	0.568	0.708	0.821
Qts:	0.331	0.534	0.659	0.756
Pmax, watts:	500	400	300	200
EXmax, mm:	12.5	12.64	12.73	10.37

Model:	05CVR154	05CVR124	05CVR104	05CVR84
Nominal Impedance:	4	4	4	4
SPL dB 1W/1M:	90	85.9	87.9	83.1
Displacement, cc:	3992	2001	1234	674
Displacement, cu.in.:	243.6	122.1	75.3	41.1
Hole cutout, in dia:	13 7/8	11 1/8	9 1/4	7 1/16
Mounting Depth, in.:	8 1/8	6 5/16	5 9/16	4 5/16
Revc:	6.93	7.09	6.98	7.55
VC Inductance, mH:	6.665	5.381	5.36	4.147
Sd, SqM:	0.0881	0.0531	0.0379	0.0214
BL:	25.83	17.99	16.63	12.17
Vas, Liters:	203.3	95.33	26	12.7
Vas, CuFt:	7.18	3.37	0.92	0.45
Mms, gms:	260.27	174.08	121.9	61.2
Fs:	23	24.7	40.4	46.1
Qms:	9.637	9.578	9.107	9.225
Qes:	0.39	0.593	0.781	0.902
Qts:	0.375	0.558	0.719	0.882
Pmax, watts:	500	400	300	200
EXmax, mm:	12.5	12.64	12.73	10.37