

| | | | | |
|-----------------------------|---------|--------|---------|--------|
| Model: | 05C154 | 05C124 | 05C104 | 05C84 |
| Nominal Impedance(Ohms): | 4 | 4 | 4 | 4 |
| SPL dB 1W/1M: | 90.2 | 88.4 | 87.3 | 85.6 |
| Displacement, cc: | 3260 | 1720 | 980 | 620 |
| Displacement, cu.in.: | 198.7 | 104.9 | 60 | 38 |
| Hole cutout, in dia: | 13 7/8 | 11 1/8 | 9 1/4 | 7 1/16 |
| Mounting Depth, in.: | 7 3/8 | 5 3/4 | 4 15/16 | 4 |
| Revc: | 3.32 | 6.89 | 3.7 | 3.98 |
| VC Inductance, mH: | 3.44 | 2.9 | 3.15 | 2.4 |
| Sd, m3: | 0.0856 | 0.0531 | 0.0206 | 0.0206 |
| BL: | 15.32 | 12.5 | 11.32 | 9.45 |
| Vas, Liters: | 272.329 | 127.65 | 64.38 | 19.54 |
| Vas, CuFt: | 9.62 | 4.51 | 2.27 | 0.69 |
| Moving Mass , oz.: | 7.38 | 4.06 | 3.13 | 15.8 |
| Fs: | 21.68 | 26.5 | 29.4 | 40.2 |
| Qms: | 11.2 | 9.865 | 9.65 | 10 |
| Qes: | 0.397 | 0.629 | 0.473 | 0.544 |
| Qts: | 0.383 | 0.591 | 0.451 | 0.516 |
| Peak Power Handling, watts: | 500 | 300 | 300 | 200 |
| EXmax, mm: | 11.53 | 9.76 | 9.76 | 8.76 |

| | | | | |
|-----------------------------|--------|--------|---------|--------|
| Model: | 05C158 | 05C128 | 05C108 | 05C88 |
| Nominal Impedance(Ohms): | 8 | 8 | 8 | 8 |
| SPL dB 1W/1M: | 88.8 | 88.4 | 87 | 85.4 |
| Displacement, cc: | 3260 | 1720 | 980 | 620 |
| Displacement, cu.in.: | 198.7 | 104.9 | 60 | 38 |
| Hole cutout, in dia: | 13 7/8 | 11 1/8 | 9 1/4 | 7 1/16 |
| Mounting Depth, in.: | 7 3/8 | 5 3/4 | 4 15/16 | 4 |
| Revc: | 7.49 | 6.89 | 6.91 | 7.54 |
| VC Inductance, mH: | 5.47 | 4.32 | 4.715 | 3.755 |
| Sd, m3: | 0.0856 | 0.0531 | 0.0206 | 0.0206 |
| BL: | 19.34 | 15.6 | 13.65 | 11.91 |
| Vas, Liters: | 279.34 | 127.65 | 66.71 | 21.05 |
| Vas, CuFt: | 9.86 | 4.51 | 2.36 | 0.74 |
| Moving Mass , oz.: | 7.9 | 4.06 | 2.91 | 15.8 |
| Fs: | 21.5 | 29.8 | 29.2 | 39.5 |
| Qms: | 11.42 | 9.865 | 10.377 | 8.281 |
| Qes: | 0.553 | 0.629 | 0.575 | 0.602 |
| Qts: | 0.527 | 0.591 | 0.545 | 0.561 |
| Peak Power Handling, watts: | 500 | 300 | 300 | 200 |
| EXmax, mm: | 11.53 | 9.76 | 9.76 | 8.76 |