

Product Tech Sheet

SPECIFICATIONS

Model	Frequency Response	Signal-to-Noise Ratio	THD	Channel Separation	Input Range	DC Range	Fuse Rating
D6 300.4	10 - 50k Hz	100 dB	0.03%	80 dB (min.)	0.2 - 5 V @ 20k ohms	11 - 14.5 V	60 A
D6 600.4	10 - 50k Hz	100 dB	0.03%	80 dB (min.)	0.2 - 5 V @ 20k ohms	11 - 14.5 V	90 A
D6 1000.1	10 - 500 Hz	80 dB	0.1%	n/a	0.2 - 5 V @ 20k ohms	11 - 14.5 V	120 A
D6 1500.1	10 - 500 Hz	80 dB	0.1%	n/a	0.2 - 5 V @ 20k ohms	11 - 14.5 V	160 A
D6 5.2	10 - 50k Hz	100 dB	0.03% 0.05% (sub)	80 dB (min.)	0.2 - 5 V @ 20k ohms	11 - 14.5 V	90 A

RMS POWER

Model	4 Ohm Stereo	2 Ohm Stereo	4 Ohm Mono	2 Ohm Mono	1 Ohm Mono
D6 300.4	37.5 x 4	75 x 4	150 x 2	n/a	n/a
D6 600.4	75 x 4	150 x 4	300 x 2	n/a	n/a
D6 1000.1	n/a	n/a	250 x 1	500 x 1	1000 x 1
D6 1500.1	n/a	n/a	375 x 1	750 x 1	1500 x 1
D6 5.2	60 x 5 & 70 x 2 (sub)	140 x 2 (sub only)	280 x 1 (sub only)	n/a	n/a

PHYSICAL DIMENSIONS

Model	(A) Length	(B) Width	(C) Height	Weight
D6 300.4	11.5"	12"	2.75"	11 lbs
D6 600.4	17"	12"	2.75"	15 lbs
D61000.1	11.5"	12"	2.75"	11 lbs
D61500.1	17"	12"	2.75"	15 lbs
D6 5.2	17"	12"	2.75"	15 lbs

